

**Suspension Systems**

**BalanceMaster Spring Balancers**

BalanceMaster balancers are the European market leader. With a range from 0.2kg to 180kg and strokes from 1.6m to 3m, they cover a huge variety of industrial load handling applications. Made from pressure die cast aluminium, with the tightest quality controls, BalanceMaster balancers are available from stock at PW.

Part Number	Range kg	Stroke
9311	0.4 to 1	1600
9312	1 to 2	1600
9312	2 to 3	1600
9320	1 to 2.5	2000
9321	2 to 4	2000
9322	4 to 6	2000
9323	6 to 8	2000
9331	2 to 4	2500
9332	4 to 6	2500
9333	6 to 8	2500
9334	8 to 10	2500
9335	10 to 14	2500
9341	2 to 4 (with stop device)	2500
9342	4 to 6 (with stop device)	2500
9343	6 to 8 (with stop device)	2500
9344	8 to 10 (with stop device)	2500
9354	4 to 7	2000
9355	7 to 10	2000
9356	10 to 14	2000
9357	14 to 18	2000
9358	18 to 22	2000
9359	22 to 25	2000
9361	10 to 15	2000
9362	15 to 20	2000
9363	20 to 25	2000
9364	25 to 30	2000
9365	30 to 35	2000
9366	35 to 45	2000
9367	45 to 55	2000
9368	55 to 65	2000
9369	65 to 75	2000
9370	75 to 90	2000
9371	90 to 105	2000



**Nylon Body**

9300	0.2 to 0.5 Nylon Cable	1600
9300/1	0.2 to 0.5 Stainless steel cable	1600
9301	0.4 to 1	1600
9302	1 to 2	1600
9303	2 to 3	1600



**Hose Balancers**

Various	0.4 to 3.0	900 - 1350
---------	------------	------------

**Options**

Rotary Insulated Hook ( option RI)
Remote from Floor ( Option B) 9361 - 71
Remote from Floor ( Option B) 9401-05, 9431-33
Remote from Floor ( Option B) 9411-14,22-26,34-44,51-56



Other balancers with longer stroke available on request